



The Electricians' Choice



METAL CLAD SWITCHED DISCONNECTOR & FUSED DISCONNECTOR

- > The range includes 32 / 63 / 80 / 100 / 125A.
- > Isolator switch, AC 23A allows safe operation with even highly inductive loads (motors, etc.).
- > Powder coated, mild steel enclosures, finish to RAL7035.
- > Ingress Protection Rating - IP65.
- > Padlockable in the 'OFF' position & door interlocked in the 'ON' position.



The Electricians' Choice

Metal Clad Switched Disconnecter



Switch Rating	Part Number	Description	Dimensions (HWD)
32A	IS324P	Steel Rotary Isolator 32A 4P AC23A	250x250x150mm
63A	IS634P	Steel Rotary Isolator 63A 4P AC23A	250x250x150mm
80A	IS804P	Steel Rotary Isolator 80A 4P AC23A	250x250x150mm
100A	IS1004P	Steel Rotary Isolator 100A 4P AC23A	300x250x150mm
125A	IS1254P	Steel Rotary Isolator 125A 4P AC23A	300x250x150mm

Metal Clad Fused Disconnecter



Fuse Rating / Fuse Type	Part Number	Description	Dimensions (HWD)
32A gG	FIS324P	Steel Fused Switch 32A 4P AC23A	300x250x150mm
63A gG	FIS634P	Steel Fused Switch 63A 4P AC23A	400x300x150mm
80A gG	FIS804P	Steel Fused Switch 80A 4P AC23A	400x300x150mm
63A gG/80A gG	FIS63804P	Steel Fused Switch 63A, 80A 4P AC23A	400x300x150mm
100A gG	FIS1004P	Steel Fused Switch 100A 4P AC23A	500x300x150mm
125A aM	FIS1254P	Steel Fused Switch 125A 4P AC23A	500x300x150mm
100A gG/125A aM	FIS1001254P	Steel Fused Switch 100A, 125A 4P AC23A	500x300x150mm



LEWDEN LTD
Unit 4, Bradbury Drive,
Springwood Industrial Estate,
Braintree
Essex
CM7 2SD

Tel.: +44 (0) 1376 336 200
Fax: +44 (0) 1376 322 161
sales@lewden.co.uk

www.lewden.com



For instant access to technical support through our team of expert engineers.